



FDL6500LE3

Diesel

Portable Generators



GENERAL SPECIFICATIONS

Engine Model :	186FA
Stand By kVA:	6,2
Stand By kW :	5
Prime kVA:	5,6
Prime kW :	4,5
Rated Current :	8

- 1) Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.
- 2) Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

TECHNICAL SPECIFICATIONS

Maximum Power	kW / kVA	5 / 6,2
Continuous Power	kW / kVA	4,5 / 5,6
Rated Current		8
Number of phases		3 (three-phase)
Voltage	V	230 / 400
Frequency		50
Display		Digital
Engine Type		Single Cylinder Air Cooled
Engine Model		186FA
Engine Power	Hp	10
Displacement		418
Starting System		Recoil / Electric
Fuel Type		Diesel
Fuel Tank Capacity	Lt	12,5
Fuel Consumption	Lt / Hour	1,6
Oil Capacity	Lt	1,65
Oil Type		15W40
Noise Level	dBA-7m	82
Weight	Kg	112
Dimensions (LxDxH)	mm	800x520x600

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

☎ 0850 222 86 28

✉ info@fullgenerator.com

▶ full generator

📷 full_generator

📺 /fullgenerator

www.fullgenerator.com