



FDL9000SC

Diesel

Portable Generators



GENERAL SPECIFICATIONS

Engine Model :	192F
Stand By kVA:	8,5
Stand By kW :	6,8
Prime kVA:	7,9
Prime kW :	6,3
Rated Current :	27,4

- 1) Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.
- 2) Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

TECHNICAL SPECIFICATIONS

Maximum Power	kw / kVA	6,8 / 8,5
Continuous Power	kw / kVA	6,3 / 7,9
Rated Current		27,4
Number of phases		1 (Single phase)
Voltage	V	230
Frequency		50
Display		Digital
Engine Type		Single Cylinder Air Cooled
Engine Model		192F
Engine Power	Hp	12
Displacement		499
Starting System		Recoil / Electric
Fuel Type		Diesel
Fuel Tank Capacity	Lt	25
Fuel Consumption	Lt / Hour	2
Oil Capacity	Lt	1,65
Oil Type		15W40
Noise Level	dBA-7m	71
Weight	Kg	160
Dimensions (LxDxH)	mm	900x520x700

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

☎ 0850 222 86 28

✉ info@fullgenerator.com

▶ full generator

📷 full_generator

📺 /fullgenerator

www.fullgenerator.com