



FGL10000LE3

Gasoline

Portable Generators



GENERAL SPECIFICATIONS

Engine Model : 460	460
Stand By kVA: 10	10
Stand By kW : 8	8
Prime kVA: 9,4	9,4
Prime kW : 7,5	7,5
Rated Current : 13,5	13,5

- 1) Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.
- 2) Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

TECHNICAL SPECIFICATIONS

Maximum Power	kW / kVA	8 / 10
Continuous Power	kW / kVA	7,5 / 9,4
Rated Current		13,5
Number of phases		3 (three-phase)
Voltage	V	230 / 400
Frequency		50
Display		Digital
Engine Type		Single Cylinder Air Cooled
Engine Model		460
Engine Power	Hp	18
Displacement		460
Starting System		Recoil / Electric
Fuel Type		Gasoline
Fuel Tank Capacity	Lt	28
Fuel Consumption	Lt / Hour	3
Oil Capacity	Lt	1,3
Oil Type		15W40
Noise Level	dBA-7m	75
Weight	Kg	87
Dimensions (LxDxH)	mm	720x530x610

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

☎ 0850 222 86 28

✉ info@fullgenerator.com

▶ full generator

📷 full_generator

📺 /fullgenerator

www.fullgenerator.com