



FGL5000LE

Gasoline

Portable Generators



GENERAL SPECIFICATIONS

Engine Model :	225
Stand By kVA:	4,75
Stand By kW :	3,8
Prime kVA:	4,38
Prime kW :	3,5
Rated Current :	15,2

- 1) Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.
- 2) Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

TECHNICAL SPECIFICATIONS

Maximum Power	kW / kVA	3,8 / 4,75
Continuous Power	kW / kVA	3,5 / 4,38
Rated Current		15,2
Number of phases		1 (Single phase)
Voltage	V	230
Frequency		50
Display		Analog
Engine Type		Single Cylinder Air Cooled
Engine Model		225
Engine Power	Hp	7,5
Displacement		223
Starting System		Recoil / Electric
Fuel Type		Gasoline
Fuel Tank Capacity	Lt	28
Fuel Consumption	Lt / Hour	1,3
Oil Capacity	Lt	0,6
Oil Type		15W40
Noise Level	dBA-7m	72
Weight	Kg	54
Dimensions (LxDxH)	mm	620x470x530

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

☎ 0850 222 86 28

✉ info@fullgenerator.com

▶ full generator

📷 full_generator

📺 /fullgenerator

www.fullgenerator.com