

FULL

GENERATOR

FDL16500SC

Diesel

Portable Generators



GENERAL SPECIFICATIONS

Engine Model :	292FA
Stand By kVA:	16,25
Prime kVA:	15
Rated Current :	52

- 1) Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.
- 2) Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

TECHNICAL SPECIFICATIONS

Maximum Power	kW / kVA	13 / 16,25
Continous Power	kW / kVA	12 / 15
Rated Current	A	52
Number of phases		1 (Single phase)
Voltage	V	230
Frequency		50
Display		Dijital
Engine Type		Double Cylinder Air Cooled
Engine Model		292FA
Engine Power	hp	22
Displacement		1064
Starting System		Electric
Fuel Type		Diesel
Fuel Tank Capacity	lt	50
Fuel Consumption	lt / hour	4
Oil Capacity	lt	3
Oil Type		15W40
Noise Level	dB(A)-7m	85
Weight	kg	295
Dimensions (LxDxH)	mm	1145 x 750 x 975

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

☎ 0850 222 86 28

✉ info@fullgenerator.com

▶ full generator

📷 full_generator

📺 /fullgenerator

www.fullgenerator.com