

FULL

GENERATOR

FDL16500SE

Diesel

Portable Generators



GENERAL SPECIFICATIONS

| | |
|-----------------|-------|
| Engine Model : | 292FA |
| Stand By kVA: | 16,25 |
| Prime kVA: | 15 |
| Rated Current : | 52 |

- 1) Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.
- 2) Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

TECHNICAL SPECIFICATIONS

| | | |
|--------------------|-----------|----------------------------|
| Maximum Power | kW / kVA | 13 / 16,25 |
| Continous Power | kW / kVA | 12 / 15 |
| Rated Current | A | 52 |
| Number of phases | | 1 (Single phase) |
| Voltage | V | 230 |
| Frequency | | 50 |
| Display | | Dijital |
| Engine Type | | Double Cylinder Air Cooled |
| Engine Model | | 292FA |
| Engine Power | hp | 22 |
| Displacement | | 1064 |
| Starting System | | Electric |
| Fuel Type | | Diesel |
| Fuel Tank Capacity | lt | 50 |
| Fuel Consumption | lt / hour | 4 |
| Oil Capacity | lt | 3 |
| Oil Type | | 15W40 |
| Noise Level | dB(A)-7m | 85 |
| Weight | kg | 195 |
| Dimensions (LxDxH) | mm | 925 x 590 x 800 |

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

☎ 0850 222 86 28

✉ info@fullgenerator.com

▶ full generator

📷 full_generator

📺 /fullgenerator

www.fullgenerator.com