# FDL-16500SC

Portable Generators




## GENERAL SPECIFICATIONS

| | |
|---|---|
| Engine Model | 292FA |
| Standby (kVA) | 16.25 kVA |
| Prime (kVA) | 15 kVA |
| Continuous Output Current (Ampere) | 52 |

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Maximum Power (kW/kVA) | 13 / 16.25 |
| Continuous Power (kW/kVA) | 12 / 15 |
| Number of phases | 1 (Single-phase) |
| Output Voltage | 230 Volt |
| Frequency | 50 Hertz |
| Display | Dijital |
| Cylinders / Cooling | Twin-cylinder, air-cooled |
| Motor Power | 22 |
| Cylinder Displacement | 1064 L |
| Way of Working | With a starter motor |
| Fuel Type | Diesel |
| Fuel Tank Capacity | 50 L |
| Fuel Consumption | 4 Litre per Hour |
| Crankcase Oil Capacity (Lt) | 3 L |
| Oily Type | 15W40 |
| Sound Level | 85 A-weighted Decibel |
| Weight | 295 kg |
| Dimensions | 1145 x 750 x 975 |

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator
www.fulljenerator.com