FDL-16500SE

Portable Generators



GENERAL SPECIFICATIONS

Engine Model	292FA
Standby (kVA)	16.25 kVA
Prime (kVA)	15 kVA
Continuous Output Current (Ampere)	52

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	13 / 16.25
Continuous Power (kW/kVA)	12 / 15
Number of phases	1 (Single-phase)
Output Voltage	230 Volt
Frequency	50 Hertz
Display	Digital
Cylinders / Cooling	Twin-cylinder, air-cooled
Motor Power	22
Cylinder Displacement	1064 L
Way of Working	With a starter motor
Fuel Type	Diesel
Fuel Tank Capacity	50 L
Fuel Consumption	4 Litre per Hour
Crankcase Oil Capacity (Lt)	3 L
Oily Type	15W40
Sound Level	85 A-weighted Decibel
Weight	195 kg
Dimensions	925 x 590 x 800

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator
www.fulljenerator.com