FULL GENERATOR

FDL-6500LE

Portable Generators



GENERAL SPECIFICATIONS

Engine Model	186FA
Standby (kVA)	6.2 kVA
Standby (kW)	5 kW
Prime (kVA)	5.6 kVA
Prime (kW)	4.5 kW
Continuous Output Current (Ampere)	19.6

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	5 / 6.2
Continuous Power (kW/kVA)	4.5 / 5.6
Number of phases	1 (Single-phase)
Output Voltage	230 Volt
Frequency	50 Hertz
Display	Digital
Cylinders / Cooling	Single-Cylinder Air-Cooled
Motor Power	10
Cylinder Displacement	418 L
Way of Working	Recoil / Electric Start
Fuel Type	Diesel
Fuel Tank Capacity	12.5 L
Fuel Consumption	1.6 Litre per Hour
Crankcase Oil Capacity (Lt)	1.65 L
Oily Type	15W40
Sound Level	82 A-weighted Decibel
Weight	112 kg
Dimensions	800x520x600

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator
www.fulljenerator.com