FDL-9000SC

Portable Generators



GENERAL SPECIFICATIONS

Engine Model	192F
Standby (kVA)	8.5 kVA
Standby (kW)	6.8 kW
Prime (kVA)	7.9 kVA
Prime (kW)	6.3 kW
Continuous Output Current (Ampere)	27.4

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	6.8 / 8.5
Continuous Power (kW/kVA)	6.3 / 7.9
Number of phases	1 (Single-phase)
Output Voltage	230 Volt
Frequency	50 Hertz
Display	Digital
Cylinders / Cooling	Single-Cylinder Air-Cooled
Motor Power	12
Cylinder Displacement	499 L
Way of Working	With a starter motor
Fuel Type	Diesel
Fuel Tank Capacity	25 L
Fuel Consumption	2 Litre per Hour
Crankcase Oil Capacity (Lt)	1.65 L
Oily Type	15W40
Sound Level	71 A-weighted Decibel
Weight	160 kg
Dimensions	900x520x700

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator
www.fulljenerator.com