



FDL9000SC3

Portable Generators



GENERAL SPECIFICATIONS

Maximum Power (kW/kVA)	5 / 6.2
Continuous Power (kW/kVA)	4.5 / 5.6
Continuous Output Current (Ampere)	19.6
Number of phases	1 (Single Phase)
Output Voltage	230 Volt

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.

2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Way of Working	Recoil / Electric Start
Fuel Tank Capacity	12.5 L
Fuel Consumption	1.6 Litre per Hour
Crankcase Oil Capacity (Lt)	1.65 L
Sound Level	82 A-weighted Decibel
Weight	112 kg
Dimensions	800x520x600

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

☎ 0850 222 86 28

✉ info@fullgenerator.com

▶ full generator

📷 [full_generator](https://www.instagram.com/full_generator)

📺 [/fullgenerator](https://www.facebook.com/fullgenerator)

www.fullgenerator.com