

FGL10000LE

Portable Generators



GENERAL SPECIFICATIONS

Engine Model	460
Standby (kVA)	10 kVA
Standby (kW)	8 kW
Prime (kVA)	9.4 kVA
Prime (kW)	7.5 kW
Continuous Output Current (Ampere)	32.5

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.

2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	8 / 10
Continuous Power (kW/kVA)	7.5 / 9.4
Number of phases	1 (Single-Phase)
Output Voltage	230 Volt
Frequency	50 Hertz
Display	Digital
Cylinders / Cooling	Single-Cylinder, Air-Cooled
Motor Power	18
Cylinder Displacement	460 L
Way of Working	Recoil / Electric Start
Fuel Type	Gasoline
Fuel Tank Capacity	28 L
Fuel Consumption	3 Litre per Hour
Crankcase Oil Capacity (Lt)	1.3 L
Oily Type	15W40
Sound Level	75 A-weighted Decibel
Weight	87 kg
Dimensions	720x530x610