FULL GENERATOR

FGL-12000LE

Portable Generators



GENERAL SPECIFICATIONS

Engine Model	GK500
Standby (kVA)	11.9 kVA
Standby (kW)	9.5 kW
Prime (kVA)	11.3 kVA
Prime (kW)	9 kW
Continuous Output Current (Ampere)	39.1

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	9.5 / 11.9
Continuous Power (kW/kVA)	9 / 11.3
Number of phases	1 (Single-Phase)
Output Voltage	230 Volt
Frequency	50 Hertz
Display	Digital
Cylinders / Cooling	1 Cylinder, 500 cc
Motor Power	20
Way of Working	Recoil / Electric Start
Fuel Type	Gasoline
Fuel Tank Capacity	28 L
Fuel Consumption	3.2 Litre per Hour
Crankcase Oil Capacity (Lt)	1.3 L
Oily Type	15W40
Sound Level	84 A-weighted Decibel
Weight	92 kg
Dimensions	720x530x610

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator
www.fulljenerator.com