FGL-3500IS

Portable Generators



GENERAL SPECIFICATIONS

Engine Model	160-Vi
Standby (kVA)	3.5 kVA
Standby (kW)	2.8 kW
Prime (kVA)	3.2 kVA
Prime (kW)	2.5 kW
Continuous Output Current (Ampere)	13.8

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	2.8 / 3.5
Continuous Power (kW/kVA)	2.5 / 3.2
Number of phases	1 (Single-Phase)
Output Voltage	230 Volt
Frequency	50 Hertz
Display	Analog
Cylinders / Cooling	1 Cylinder 163cc
Motor Power	7
Way of Working	İpli
Fuel Type	Gasoline
Fuel Tank Capacity	8 L
Fuel Consumption	1 Litre per Hour
Crankcase Oil Capacity (Lt)	0.5 L
Oily Type	15W40
Sound Level	58 A-weighted Decibel
Weight	28 kg
Dimensions	620x470x530

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator

www.fulljenerator.com

www.railjenerator.com