FGL-7000İSE

Portable Generators



GENERAL SPECIFICATIONS

Engine Model	330V-i
Standby (kVA)	6.5 kVA
Standby (kW)	5.2 kW
Prime (kVA)	6 kVA
Prime (kW)	4.8 kW
Continuous Output Current (Ampere)	26

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	5.2 / 6.5
Continuous Power (kW/kVA)	4.8 / 6
Number of phases	1 (Single-Phase)
Output Voltage	230 Volt
Frequency	50 Hertz
Display	Digital
Cylinders / Cooling	1 Cylinder 327cc
Motor Power	7.5
Way of Working	Recoil / Electric Start
Fuel Type	Gasoline
Fuel Tank Capacity	14 L
Fuel Consumption	1.3 Litre per Hour
Crankcase Oil Capacity (Lt)	0.6 L
Oily Type	15W40
Sound Level	72 A-weighted Decibel
Weight	54 kg
Dimensions	620x470x530

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator
www.fulljenerator.com